

Industrial Stainless Steel Gauges 2.5"

Brand: Reotemp



Short Description

Reotemp's Series PM25 features a stainless steel case, tube and socket, making the gauges resistant to corrosion from both environment and media. Liquid filling is recommended for severe service. The economical and attractive crimp ring design, along with a variety of convenient panel mounting adapters, make this popular gauge the right choice for many applications. All-Welded Stainless Steel Construction Field Fillable Case, Nema 4X/IP65 Economical Crimped Gauge with Heavy Duty Case Design Ideal for Both Indoor and Outdoor Applications

Description

Accuracy $\pm 1.6\%$ ASME Grade B+, EN 837-1 Ambient Limits $-40^{\circ}\text{F}/150^{\circ}\text{F}$ Process Limits $-40^{\circ}\text{F}/250^{\circ}\text{F}$ Process Limits with Diaphragm Seal Available with diaphragm seal, call to inquire. Wetted Materials Tube: 316SS Socket: 316SS Lens Polycarbonate (Standard), Tempered Glass, Laminated Safety Glass Other Materials Case: 304SS Ring: 304SS Dial: White Aluminum, Black Letters Case-to-Socket: Laser Welded Fillable Yes Maximum Working Pressure Stable = 100% Momentary = 130% of scale Environmental Protection NEMA 4X/IP65 Weight 2.5" = 0.35 lbs (0.5 lbs filled)