

Repairable Industrial Stainless/Brass Gauges

Brand: Reotemp



Short Description

REOTEMP's Series PG25/40S gauges are an economical choice where ambient corrosion and vibration are of concern. The stainless steel case and ring offer excellent corrosion resistance, and are fillable for applications with vibration. The PG25/40S is suitable for all fluids compatible with copper alloys. Stainless Steel Case Copper Alloy Wetted Parts Glycerin Filled or Dry/Fillable Removable Bayonet, Adjustable Pointer ASME B40.100 Design

Description

Construction Materials Non Wetted Case: 304SS Ring: 304SS Dial: White Aluminum, Black Letters Wetted Tube: Copper Alloy Socket: Copper Alloy Case-to-Socket Screw Connection Lens Tempered Safety Glass (Std.), Plastic, or Laminated Safety Glass Temperature Limits Ambient -40°F to 140°F Process -40°F to 150°F Process When Assembled with a Diaphragm Seal Not Recommended for Diaphragm Seal Mounting. See PR Model Gauges for Diaphragm Seal Mounting. Accuracy: 2.5" = 2 – 1 – 2% (ASME Grade A), 4" = 1% (ASME Grade 1A) Fillable: Yes Restrictor Screw: Yes, Removable Max Working Pressure: Stable = 100%, Momentary = 130% of scale Weight: 2.5" = 0.4 lbs (0.6 filled), 4" = 1.3 lbs (2 filled)