



OPTIFLEX 7200 C/F/S/D Technical Datasheet

Guided radar (TDR) level transmitter for liquids in storage and process applications

- Premium device for level and interface measurement in the chemical, oil and gas industries
- Extensive choice of probes for all applications with ± 2 mm / 0.08" accuracy
- SIL 2/3-certified current and relay outputs


HART
COMMUNICATION PROTOCOL



1	Product features	3
1.1	The modular TDR level transmitter for storage and process applications	3
1.2	Applications	4
1.3	Product family	5
1.4	Application table for probe selection	8
1.5	Measuring principle.....	8
2	Technical data	11
2.1	Technical data.....	11
2.2	Minimum power supply voltage	24
2.3	Process pressure and process connection temperature limits.....	25
2.4	Measurement limits	28
2.5	Dimensions and weights	35
2.5.1	General notes.....	35
2.5.2	Primary components	35
2.5.3	Signal converter and probe electronics options	36
2.5.4	Process connection options.....	44
2.5.5	Probe options	46
2.5.6	Weather protection option	53
3	Installation	55
3.1	Intended use	55
3.2	How to prepare the tank before you install the device	55
3.2.1	General information for nozzles.....	55
3.3	Installation recommendations for liquids.....	58
3.3.1	General requirements	58
3.3.2	Installation in standpipes (stilling wells and bypass chambers)	59
4	Electrical connections	61
4.1	Electrical installation: 2-wire, loop-powered	61
4.1.1	Compact version	61
4.1.2	Remote version	62
4.2	Non-Ex devices	64
4.3	Devices for hazardous locations	66
4.4	Networks	66
4.4.1	General information.....	66
4.4.2	Point-to-point networks	66
4.4.3	Multi-drop networks	67

1.1 The modular TDR level transmitter for storage and process applications

OPTIFLEX 7200 is the premium device for level and interface measurement in the chemical, oil and gas industries. It has a large range of probe options and a modular design that permits it to be installed in small spaces.



- ① Extensive choice of probes for all applications with ± 2 mm / 0.08" accuracy. It is also possible to measure interface in "reversed interface" conditions (e.g. water / CS_2).
- ② Aluminium or stainless steel housing
- ③ Optional LCD screen with 4-button keypad
- ④ Quick coupling system: converter is rotatable and removable under process conditions

The display can be ordered with the device or as an accessory. It shows measurement data on a 128 x 64 pixel screen. The configuration menu permits the device to be set up in a small number of intuitive steps.

Highlights

- Process conditions up to +250°C / +482°F and 100 barg / 1450 psig
- 2-wire 4...20 mA (HART® 7) with optional second output (current or switch/relay)
- Measuring distance up to 60 m / 196.85 ft; level and interface measurement
- SIL 2/3-compliant: 1 current output, 2 current outputs, or 1 current output + 1 switch output (relay)
- Stainless steel housing for corrosive environment
- Real-time clock for event logging
- 3-year warranty
- Can measure interface when the top product has a depth of only 50 mm / 1.97"
- Optional ceramic process seal system for demanding process conditions
- Various converter and electronic versions to facilitate access to the device:
 - Remote converter up to 115 m / 377.30 ft from the probe
 - Horizontal or vertical housing to suit every installation
- Diagnosis functions supply data according to NAMUR NE 107

- PACTware™, HART® DD and DTM provided free of charge with full functionality
- Quick setup assistant for easy commissioning
- Display keypad directly accessible without opening the cover

Industries

- Chemical & Petrochemical
- Oil & Gas
- Power


Applications

Liquids in storage and process applications: ≤ 60 m / 196.85 ft; $\leq +250^{\circ}\text{C}$ / $+482^{\circ}\text{F}$; ≤ 100 barg / 1450 psig

- Storage – Chemical – Solvents, alcohols, Acids, bases, Ethylene, Propylene, Additives, CO_2 , NH_3 etc.
- Storage & reactors – Chemical – Foaming agents
- Storage & process & reactors – Oil & Gas – Hydrocarbons
- Storage – Oil & Gas – Liquefied gases
- Remote level control on a chemical production site
- Monitoring level in a plasticizer tank with agitator (stilling well installation)
- Hydrocarbon level measurement in a refinery


1.2 Applications

1. Level measurement of liquids



The level transmitter can measure the level of a wide range of liquid products on a large variety of installations within the stated pressure and temperature range. It does not require any calibration: it is only necessary to adapt the probe length and do a short configuration procedure.

2. Volume measurement



A conversion table (strapping table) function is available in the configuration menu for volume or mass measurement. Up to 30 volume values can be related to level values. For example:

Level ① = 2 m / Volume ① = e.g. 0.7 m³

Level ② = 10 m / Volume ② = e.g. 5 m³

Level ③ = 20 m / Volume ③ = e.g. 17 m³

This data permits the device to calculate volumes between strapping table entries.

1.3 Product family

OPTIFLEX 1100 C

for continuous measurement of liquids and solids up to 16 barg (232 psig) and +100°C (+212°F)



OPTIFLEX 1100 C is a 2-wire TDR level transmitter for measuring distance, level, volume and mass of liquids and solids. Its simple, compact design allows technicians to quickly assemble the probe and attach it to a threaded connection. It is an affordable solution for applications that do not require a high level of accuracy and is also an excellent alternative to traditional level controls such as RF Capacitance, conductive and DP transmitters.

It is ideal for level measurement in buffer tanks, collectors and simple process applications and silo level monitoring in quarrying and agriculture.

OPTIFLEX 3200 C/F**for liquids with hygienic requirements up to 40 barg (580 psig) and +150°C (+302°F)**

This TDR level transmitter, with its hygienic design, is ideal for measuring measure level and interface in small vessels and tanks with CIP/SIP cycles. It can also be installed in tanks up to 4 m / 13.12 ft high.

This device has a single rod probe made of stainless steel with a surface roughness of $R_a < 0.76 \mu\text{m}$ / $30 \mu\text{in}$ – AARH, and large selection of process connections for hygienic applications.

OPTIFLEX 6200 C/F**for solids from granulates to powders up to 40 barg (580 psig) and +200°C (392°F)**


This level transmitter measures granulates and powders in deep pits or high containers. It has a maximum measuring distance of 40 m / 131.2 ft.

Its durable design can withstand traction loads up to 3500 kg (7700 lb) and electrostatic discharges up to 30 kV. A specially developed set of algorithms also permits the device to accurately measure the level of low-reflective media.

OPTIFLEX 7200 C/F/S/D**for liquids in storage and process applications up to 100 barg (1450 psig) and 250°C (482°F)**

The OPTIFLEX 7200 is designed specifically for measuring level and interface in the chemical, oil and gas industries. It can be used in high tanks (max. height 60 m / 197 ft) and pressure vessels.

It has many probe options, making it suitable for a wide range of process conditions. It can also measure volatile products such as carbon disulphide using the reversed interface probe.

OPTIFLEX 8200 C/F/S**for liquids at high temperature and pressure up to 320 barg (4641 psig) and 315°C (599°F)**

This level transmitter is designed specifically for measuring level and interface in extreme conditions such as boilers in the power, oil and gas industries.

It can be used in very high tanks (max. height 60 m / 197 ft). It can be equipped with a stainless steel housing for corrosive environments.

1.4 Application table for probe selection

	Double rod	Single rod	Single rod (segmented)	Coaxial Ø22 mm	Coaxial Ø22 mm (segmented)	Coaxial Ø45 mm	Double cable	Single cable	Reversed interface
--	------------	------------	------------------------	----------------	----------------------------	----------------	--------------	--------------	--------------------

Maximum probe length, L

4 m / 13 ft	■	■							■
6 m / 20 ft			■	■	■	■			
14 m / 46 ft							■		
60 m / 197 ft								■	

Liquids

Liquid application	■	■	■	■	■	■	■	■	■
LPG, LNG	■	①	①	■	■	■	■	①	
Highly viscous liquids		■	■					■	
Highly crystallising liquids		■	■					■	
Highly corrosive liquids		②		③		③		③	
Foam		■	■	■	■	■		■	
Water / heavy liquid with low dielectric constant (e.g. water / CS ₂)									■
Agitated liquids	④	④	④	④	④	④	④	④	④
Spray in tank		①	①	■	■	■		①	
Storage tanks	■	■	■	■	■	■	■	■	■
Installation in bypass chamber or stilling well	■	■	■	■	■	■	■	■	■
Small diameter nozzles and long nozzles	■	④	④	■	■	■		④	

■ standard ■ optional □ on request

- ① Install the device in a stilling well or a bypass chamber
- ② Use a fully TFM-T62 PTFE-coated probe
- ③ Use a probe made of HASTELLOY® C-22®
- ④ Use this probe with an anchor fitting. For more data, refer to the handbook.

1.5 Measuring principle

This Guided Radar (TDR) level meter has been developed from a proven technology called Time Domain Reflectometry (TDR).

The device transmits low-intensity electromagnetic pulses of approximately one nanosecond width along a rigid or flexible conductor. These pulses move at the speed of light. When the pulses reach the surface of the product to be measured, the pulses are reflected with an intensity that depends on the dielectric constant, ϵ_r , of the product (for example, water has a high dielectric constant and reflects the pulse back to the signal converter at 80% of its original intensity).

The device measures the time from when the pulse is emitted to when it is received: half of this time is equivalent to the distance from the reference point of the device (the flange facing) to the surface of the product. The time value is converted into an output current of 4...20 mA and/or a digital signal.

Dust, foam, vapor, agitated surfaces, boiling surfaces, changes in pressure, changes in temperature and changes in density do not have an effect on device performance.

The illustration that follows shows a snapshot of what a user would see on an oscilloscope, if the level of one product is measured.

Level measurement principle (direct mode)




Figure 1-1: Level measurement principle

- ① Time 0: The electromagnetic (EM) pulse is transmitted by the converter
- ② Time 1: The pulse goes down the probe at the speed of light in air, V_1
- ③ Time 2: The pulse is reflected
- ④ Time 3: The pulse goes up the probe at speed, V_1
- ⑤ Time 4: The converter receives the pulse and records the signal
- ⑥ The EM pulse moves at speed, V_1
- ⑦ Transmitted EM pulse
- ⑧ Half of this time is equivalent to the distance from the reference point of the device (the flange facing) to the surface of the product
- ⑨ Received EM pulse

Level and interface measurement principle (direct measurement)

The illustration that follows shows a snapshot of what a user would see on an oscilloscope, if the level and/or interface of products are measured.

The dielectric constant of the top liquid must be less than the dielectric constant of the bottom liquid. If not, or if there is too small a difference, the device may not measure correctly.




Figure 1-2: Level and interface measurement principle (2 liquids in the tank)

- ① Time 0: The electromagnetic (EM) pulse is transmitted by the converter
- ② Time 1: The pulse goes down the probe at the speed of light in air, V1
- ③ Time 2: Part of the pulse is reflected at the surface of the top liquid, the remaining pulse goes down the probe
- ④ Time 3: Part of the pulse goes up the probe at speed, V1. The remaining pulse goes down the probe at the speed of light in the top product, V2
- ⑤ Time 4: The converter receives part of the pulse and records the signal. The remaining pulse is reflected at the interface of the 2 liquids
- ⑥ Time 5: The remaining pulse goes up the probe at speed, V2
- ⑦ Time 6: The remaining pulse goes up the probe at speed, V1
- ⑧ Time 7: The converter receives the remaining pulse and records the signal
- ⑨ The EM pulse moves at speed, V1
- ⑩ The EM pulse moves at speed, V2
- ⑪ Transmitted EM pulse
- ⑫ Received EM pulse (distance to the top liquid)
- ⑬ Received EM pulse (distance to the interface of 2 liquids)

Level measurement principle (TBF measurement)

If products have a very low dielectric constant ($\epsilon_r < 1.6$), only a small part of the EM pulse is reflected at the surface of the product. Most of the pulse is reflected at the probe end. TBF (tank bottom following) mode is used to measure the distance to the product surface.

TBF mode (indirect measurement) compares:

- The time for the pulse to go to the probe end and go back to the converter when the tank is empty.
- The time for the pulse to go to the probe end and go back to the converter when the tank is full or partially filled.

The level of the product in the tank can be calculated from the time difference.

2.1 Technical data

- The following data is provided for general applications. If you require data that is more relevant to your specific application, please contact us or your local sales office.
- Additional information (certificates, special tools, software,...) and complete product documentation can be downloaded free of charge from the website (Downloadcenter).

Converter

Measuring system

Application	Level and interface measurement of liquids and pastes
Measuring principle	TDR (time domain reflectometry) - guided radar
Primary measured values	Distance and interface distance
Secondary values	Level, interface level, volume and mass
Construction	Compact (C) version: Measuring probe attached directly to the signal converter
	Remote (F) version: Measuring probe installed on a tank and connected by a signal cable (max. length 100 m / 328 ft) to the signal converter
	Sensor extension (S) version: Measuring probe installed on a tank and connected by a coaxial cable (max. length 15 m / 49 ft) to the signal converter
	Double sensor extension (D) version: Measuring probe installed on a tank and connected by a coaxial cable (max. length 15 m / 49 ft) to the probe electronics housing. The probe electronics housing is connected by a signal cable (max. length 100 m / 328 ft) to the signal converter.

Operating conditions

Ambient temperature	-40...+80°C / -40...+176°F Integrated LCD display: -20...+60°C / -5...+140°F; if the ambient temperature is not in these limits, the display switches off. The device continues to operate correctly.
Storage temperature	-50...+85°C / -58...+185°F (min. -40°C / -40°F for devices with the integrated LCD display option)
Ingress protection	IEC 60529: IP66 / IP68 (continuous immersion at a depth of 1.5 m for 2 weeks)
	NEMA 250: NEMA type 4X / 6 (housing) and type 6P (probe)

Materials

Housing	Polyester-coated aluminium or stainless steel (1.4404 / 316L)
Cable entry	Plastic; nickel-plated brass, stainless steel

Electrical connections

Power supply, output 1 (4...20 mA/HART output)	Non-Ex / Ex i: 11.5...30 V DC; min./max. value for an output of 22 mA at the terminals
	Ex d: 13.5...34 V DC; min./max. value for an output of 22 mA at the terminals
Power supply, optional output 2 (4...20 mA output)	Non-Ex / Ex i: 11.5...30 V DC; min./max. value for an output of 22 mA at the terminals (additional power supply needed – output only)
	Ex d: 11.5...34 V DC; min./max. value for an output of 22 mA at the terminals (additional power supply needed – output only)
Power supply, optional input 2 (switch output - relay)	Non-Ex / Ex i: 11.5...30 V DC / 30 mA
	Ex d: 11.5...34 V DC / 30 mA

Current output load	Non-Ex / Ex i: $R_L [\Omega] \leq ((U_{ext} - 11.5 \text{ V})/22 \text{ mA})$. For more data, refer to <i>Minimum power supply voltage</i> on page 24.
	Ex d, output 1: $R_L [\Omega] \leq ((U_{ext} - 13.5 \text{ V})/22 \text{ mA})$. For more data, refer to <i>Minimum power supply voltage</i> on page 24.
	Ex d, output 2: $R_L [\Omega] \leq ((U_{ext} - 11.5 \text{ V})/22 \text{ mA})$. For more data, refer to <i>Minimum power supply voltage</i> on page 24.
Cable entry	M20×1.5; ½ NPT
Cable gland	Standard: none
	Options: M20×1.5, others are available on request
	Cable diameter, output 1: non-Ex / Ex i: 6...7.5 mm / 0.24...0.30"; Ex d: 7...10 mm / 0.28...0.39"; Cable diameter, output 2: non-Ex / Ex i: 6...12 mm / 0.24...0.47"; Ex d: 7...12 mm / 0.28...0.47"
Signal cable – remote version	None for non-Ex devices (4-wire shielded cable of max. length 100 m / 328 ft to be supplied by the customer). Supplied with all Ex-approved devices. For more data, refer to the handbook
Cable entry capacity (terminal)	0.5...2.5 mm ²

Input and output

Measured variable	Time between the emitted and received signal
Current output / HART®	
Output 1 signal	4...20 mA HART® or 3.8...20.5 mA acc. to NAMUR NE 43
Output 2 signal	4...20 mA or 3.8...20.5 mA acc. to NAMUR NE 43
Resolution	±3 µA
Temperature drift (analog)	Typically 50 ppm/K
Temperature drift (digital)	Max. ±15 mm for the full temperature range
Error signal options	High: 22 mA; Low: 3.6 mA acc. to NAMUR NE 43; Hold (frozen value – not available if the output agrees with NAMUR NE 43 or the device is approved for safety-related systems (SIL))
Switch output - relay (option)	
Description	Relay (1 electrical contact, normally open). SIS 2 Sensitive Series (ELESTA GmbH).
Maximum switching capacity	Non-Ex / Ex d: 48 V AC / 6 A; 24 V DC / 6 A (according to IEC 60947-5-1)
	Ex i / Ex nA: 24 V AC / 1.1 A; 24 V DC / 1.1 A (according to IEC 60947-5-1)
Voltage range	Non-Ex / Ex d: Category AC-1: 5...48 V AC / Category DC-1: 2...24 V DC
	Ex i / Ex nA: Category AC-1: 5...24 V AC / Category DC-1: 2...24 V DC
Current range	0.003...6 A
R _{on-state}	< 100 mΩ at 6 V / 100 mA
Switching capacity range	0.04...288 W (VA)

Display and user interface

User interface options	LCD display (128 × 64 pixels in 8-step greyscale with 4-button keypad)
Languages	English, German, French, Italian, Spanish, Portuguese, Japanese, Chinese (simplified), Russian, Czech, Polish and Turkish

Approvals and certification

CE / UKCA	<p>The device meets the essential requirements of the EU Directives and UK Regulations. The manufacturer certifies successful testing of the product by applying the CE or UKCA marking.</p> <p>For more data about the European Standards and UK Designated Standards related to this device, refer to the EU and the UKCA Declarations of Conformity. You can download these documents free of charge from the website (Download Center).</p>
Vibration resistance	<p>Housing: EN 60721-3-4, Category 4M4 (5...8.51 Hz: ±3.5 mm / 8.51...200 Hz: 1g; 15g shock ½sinus: 6 ms) "C" version only: DNVGL-CG-0339, Class A (5...13.2 Hz: ±0.5 mm / 13.2...100 Hz: 0.7g) Refer to "Probe options" in this section for the vibration resistance of probes</p>
Explosion protection	
<p>ATEX (Ex ia, Ex ia/db or Ex ia/tb) EU Type Approval</p> <p>UKEX (Ex ia, Ex ia/db or Ex ia/tb) UK Type Approval</p>	<p>Compact version</p> <p>II 1/2 G Ex ia IIC T6...T* Ga/Gb; ①</p> <p>II 1/2 D Ex ia IIIC T85°C...T*°C Da/Db ②</p> <p>or...</p> <p>II 1/2 G Ex ia/db IIC T6...T* Ga/Gb; ①</p> <p>II 1/2 D Ex ia/tb IIIC T85°C...T*°C Da/Db ②</p> <p>Remote version, converter</p> <p>II 2 (1) G Ex ia [ia Ga] IIC T6...T4 Gb;</p> <p>II 2 (1) D Ex ia [ia Da] IIIC T85°C...T135°C Db</p> <p>or...</p> <p>II 2 (1) G Ex db ia [ia Ga] IIC T6...T4 Gb;</p> <p>II 2 (1) D Ex ia tb [ia Da] IIIC T80°C...T150°C Db</p> <p>Remote version, sensor</p> <p>II 1/2 G Ex ia IIC T6...T* Ga/Gb; ①</p> <p>II 1/2 D Ex ia IIIC T85°C...T*°C Da/Db ②</p>
ATEX (Ex ic or Ex ic nA) Type Approval	<p>Compact version</p> <p>II 3 G Ex ic IIC T6...T* Gc; ①</p> <p>II 3 D Ex ic IIIC T85°C...T*°C Dc ②</p> <p>or...</p> <p>II 3 G Ex ic nA IIC T6...T* Gc ①</p> <p>Remote version, converter</p> <p>II 3 G Ex ic [ic] IIC T6...T4 Gc;</p> <p>II 3 D Ex ic [ic] IIIC T85°C...T135°C Dc</p> <p>or...</p> <p>II 3 G Ex ic nA [ic] IIC T6...T4 Gc</p> <p>Remote version, sensor</p> <p>II 3 G Ex ic IIC T6...T* Gc; ①</p> <p>II 3 D Ex ic IIIC T85°C...T*°C Dc ②</p>

IECEEx	Compact version
	Ex ia IIC T6...T* Ga/Gb; ①
	Ex ia IIIC T85°C...T*°C Da/Db ②
	or...
	Ex ia/db IIC T6...T* Ga/Gb; ①
	Ex ia/tb IIIC T85°C...T*°C Da/Db ②
	or...
	Ex ic IIC T6...T* Gc; ①
	Ex ic IIIC T85°C...T*°C Dc ②
	or...
	Ex ic nA IIC T6...T* Gc ①
	Remote version, converter
	Ex ia [ia Ga] IIC T6...T4 Gb;
	Ex ia [ia Da] IIIC T85°C...T135°C Db
	or...
	Ex db ia [ia Ga] IIC T6...T4 Gb
	Ex ia tb [ia Da] IIIC T85°C...T135°C Db
	or...
	Ex ic [ic] IIC T6...T4 Gc
	Ex ic [ic] IIIC T85°C...T135°C Dc
	or...
	Ex ic nA [ic] IIC T6...T4 Gc
	Remote version, sensor
	Ex ia IIC T6...T* Ga/Gb; ①
	Ex ia IIIC T85°C...T*°C Da/Db ②
	or...
	Ex ic IIC T6...T* Gc; ①
Ex ic IIIC T85°C...T*°C Dc ②	

cQPSus – Dual Seal-approved	NEC 500 and CEC Section 18 and Annex J (Division ratings)
	Compact version
	IS, Class I, Div 1, GPS ABCD, T6...T*; ①
	IS, Class II/III, Div 1, GPS EFG, T85°C...T*°C ②
	or...
	XP-IS, Class I, Div 1, GPS A (US only) BCD, T6...T*; ①
	DIP-IS, Class II/III, Div 1, GPS EFG, T85°C...T*°C ②
	or...
	NI, Class I, Div 2, GPS ABCD, T6...T*; ①
	NI, Class II/III, Div 2, GPS FG, T85°C...T*°C ②
	Remote version, converter
	IS, Class I, Div 1, GPS ABCD, T6...T4;
	IS, Class II/III, Div 1, GPS EFG, T85°C...T135°C
	or...
	XP-IS, Class I, Div 1, GPS A (US only) BCD, T6...T4;
	DIP-IS, Class II/III, Div 1, GPS EFG, T85°C...T135°C
	or...
	NI, Class I, Div 2, GPS ABCD, T6...T4;
	NI, Class II/III, Div 2, GPS FG, T85°C...T135°C
	Remote version, sensor
IS, Class I, Div 1, GPS ABCD, T6...T*; ①	
IS, Class II/III, Div 1, GPS EFG, T85°C...T*°C ②	
or...	
NI, Class I, Div 2, GPS ABCD, T6...T*; ①	
NI, Class II/III, Div 2, GPS FG, T85°C...T*°C ②	
cQPSus – Dual Seal-approved	NEC 505 and NEC 506 (Zone ratings)
	Compact version
	Class I, Zone 0 AEx ia IIC T6...T* Ga; ①
	Zone 20, AEx ia IIIC T85°C...T*°C Da ②
	or...
	Class I, Zone 1 AEx db ia [ia Ga] IIC T6...T* Gb; ①
	Zone 21, AEx ia tb [ia Da] IIIC T85°C...T*°C Db ②
	Remote version, converter
	Class I, Zone 1 AEx ia [ia Ga] IIC T6...T4 Gb;
	Zone 21, AEx ia [ia Da] IIIC T85°C...T135°C Db
	or...
	Class I, Zone 1 AEx db ia [ia Ga] IIC T6...T4 Gb;
	Zone 21, AEx ia tb [ia Da] IIIC T85°C...T135°C Db
	Remote version, sensor
Class I, Zone 0 AEx ia IIC T6...T* Ga; ①	
Zone 20, AEx ia IIIC T85°C...T*°C Da ②	

cQPSus – Dual Seal-approved	CEC Section 18 (Zone ratings)
	Compact version
	Ex ia IIC T6...T* Ga; ①
	Ex ia IIIC T85°C...T*°C Da ②
	or...
	Ex db ia [ia Ga] IIC T6...T* Gb; ①
	Ex ia tb [ia Da] IIIC T85°C...T*°C Db ②
	Remote version, converter
	Ex ia [ia Ga] IIC T6...T4 Gb;
	Ex ia [ia Da] IIIC T85°C...T135°C Db
	or...
	Ex db ia [ia Ga] IIC T6...T4 Gb;
	Ex ia tb [ia Da] IIIC T85°C...T135°C Db
	Remote version, sensor
	Ex ia IIC T6...T* Ga; ①
Ex ia IIIC T85°C...T*°C Da ②	
NEPSI	Compact version
	Ex ia IIC T*...T6 Ga/Gb; ①
	Ex ia IIIC T ₂₀₀ 85°C...T ₂₀₀ *°C Da / Ex ia IIIC T85°C...T*°C Db ②
	or...
	Ex ia db IIC T*...T6 Ga/Gb; ①
	Ex ia IIIC T ₂₀₀ 85°C...T ₂₀₀ *°C Da / Ex tb IIIC T85°C...T*°C Db ②
	Remote version, converter
	Ex ia [ia Ga] IIC T4...T6 Gb;
	Ex ia [ia Da] IIIC T85°C...T135°C Db
	or...
	Ex db ia [ia Ga] IIC T4...T6 Gb;
	Ex ia tb [ia Da] IIIC T85°C...T135°C Db
	Remote version, sensor
	Ex ia IIC T*...T6 Ga/Gb; ①
	Ex ia IIIC T ₂₀₀ 85°C...T ₂₀₀ *°C Da / Ex ia IIIC T85°C...T*°C Db ②

KCs	Compact version
	Ex ia IIC T6...T* Ga/Gb; ①
	Ex ia IIIC T85°C...T*°C Da/Db ②
	or...
	Ex ia/db IIC T6...T* Ga/Gb; ①
	Ex ia/tb IIIC T85°C...T*°C Da/Db ②
	Remote version, converter
	Ex ia [ia Ga] IIC T6...T4 Gb;
	Ex ia [ia Da] IIIC T85°C...T135°C Db
	or...
	Ex db ia [ia Ga] IIC T6...T4 Gb
	Ex ia tb [ia Da] IIIC T85°C...T135°C Db
	Remote version, sensor
	Ex ia IIC T6...T* Ga/Gb; ①
	Ex ia IIIC T85°C...T*°C Da/Db ②
EAC-EX - pending	Compact version
	Ga/Gb Ex ia IIC T6...T* X; ①
	Da/Db Ex ia IIIC T85°C...T*°C X ②
	or...
	Ga/Gb Ex ia/db IIC T6...T* X; ①
	Da/Db Ex ia/tb IIIC T85°C...T*°C X ②
	Remote version, converter
	1Ex ia [ia Ga] IIC T6...T4 Gb X;
	Ex ia [ia Da] IIIC T85°C...T135°C Db X
	or...
	1Ex db ia [ia Ga] IIC T6...T4 Gb X;
	Ex ia tb [ia Da] IIIC T85°C...T135°C Db X
	Remote version, sensor
	Ga/Gb Ex ia IIC T6...T* X; ①
	Da/Db Ex ia IIIC T85°C...T*°C X ②
Other standards and approvals	
SIL	C (Compact) and S (Sensor Extension) versions only: SIL 2/3 (SIL3: 1oo2 architecture is necessary for homogeneous redundancy) – certified according to all the requirements in EN 61508 (Full Assessment) and for high/low continuous demand mode operation. HFT=0, SFF=93% (for non-Ex / Ex i devices with one output), 94% (for non-Ex / Ex i devices with two outputs) or 95% (for Ex d devices), type B device
EMC	Electromagnetic Compatibility (EMC) directive. The device agrees with this directive and its related standard if the device has a single probe that is installed in a metallic tank. SIL 2/3-approved devices agree with EN 61326-3-1 and EN 61326-3-2.

NAMUR	NAMUR NE 21 Electromagnetic Compatibility (EMC) of Industrial Process and Laboratory Control Equipment
	NAMUR NE 43 Standardization of the Signal Level for the Failure Information of Digital Transmitters
	NAMUR NE 53 Software and Hardware of Field Devices and Signal Processing Devices with Digital Electronics
	NAMUR NE 107 Self-Monitoring and Diagnosis of Field Devices
Conformity to construction codes	On request (for equipment used in the oil and gas industries): NACE MR0175 (ISO 15156); NACE MR0103 (ISO 17945)

Table 2-1: Technical data: Converter

- ① If the device has a ceramic process seal system and a Kalrez® gasket, then T* = T2. For all other versions, T* = T3.
- ② If the device has a ceramic process seal system and a Kalrez® gasket, then T*°C = T250°C and *°C = 250°C. If the device has a ceramic process and an FPM/FKM gasket, then T*°C = T200°C and *°C = 200°C. For all other versions, T*°C = T150°C and *°C = 150°C.

Probe options

	Single rod Ø8 mm / 0.39"		Single rod Ø10 mm / 0.32"	Single cable Ø4 mm / 0.16"
	Single-piece	Segmented	Single-piece, fully TFM-T62 PTFE coated	

Measuring system

Application	Liquids			
Measuring range	0.6...4 m / 1.97...13.12 ft	0.6...6 m / 1.97...19.69 ft	0.6...4 m / 1.97...13.12 ft	1...60 m / 3.28...196.85 ft
Dead zone	This depends on the type of probe. For more data, refer to <i>Measurement limits</i> on page 28.			

Measuring accuracy

Accuracy (in direct mode)	Standard ±2 mm / ±0.08", when distance ≤ 10 m / 33 ft; ±0.02% of measured distance, when distance > 10 m / 33 ft		
	Interface ±5 mm / ±0.2", when distance ≤ 10 m / 33 ft; ±0.05% of measured distance, when distance > 10 m / 33 ft ①		
Accuracy (in TBF mode)	±20 mm / ±0.8"		
Minimum layer (interface)	50 mm / 2"		
Resolution	0.1 mm / 0.004"		
Repeatability	±1 mm / ±0.04"		
Maximum rate of change at 4 mA	100 m/min / 328 ft/min		
Reference conditions acc. to EN 61298-1			
Temperature	+15...+25°C / +59...+77°F		
Pressure	1013 mbara ±50 mbar / 14.69 psia ±0.73 psi		
Relative air humidity (RH)	60% ±15%		
Target	Metal plate	Water	Metal plate

	Single rod Ø8 mm / 0.39"		Single rod Ø10 mm / 0.32"	Single cable Ø4 mm / 0.16"
	Single-piece	Segmented	Single-piece, fully TFM-T62 PTFE coated	

Operating conditions

Min./Max. temperature at the process connection ②	-50...+300°C / -58...+572°F	-50...+150°C / -58...+302°F	-50...+300°C / -58...+572°F
Pressure	Single PTFE process seal system or fully TFM-T62 PTFE-coated: -1...40 barg / -14.5...580 psig		
	Single ceramic process seal system: -1...100 barg / -14.5...1450 psig	—	Single ceramic process seal system -1...100 barg / -14.5...1450 psig
Viscosity (liquids only)	10000 mPa·s / 10000 cP		
Dielectric constant $\{\epsilon_r\}$	≥ 1.6 in direct mode (interface: $\epsilon_r(\text{interface}) \gg \epsilon_r(\text{level})^2$); ≥ 1.1 in TBF mode		
Vibration resistance	EN 60721-3-4, Category 4M3 (5...8.22 Hz: ± 0.75 mm / 8.22...200 Hz: 0.2g; 5g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g) ③		EN 60721-3-4, Category 4M4 (5...8.51 Hz: ± 3.5 mm / 8.51...200 Hz: 1g; 15g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g)

Materials

Probe	Stainless steel (1.4404 / 316L); HASTELLOY® C-22® [2.4602]	Stainless steel (1.4404 / 316L)	TFM-T62 PTFE-coated stainless steel (1.4404 / 316L)	Stainless steel (1.4401 / 316) ④
Gasket (process seal)	Single PTFE process seal system: FKM/FPM, Kalrez® 6375, EPDM ⑤		None	Single ceramic process seal system FKM/FPM, Kalrez® 6375, EPDM ⑤
	Single ceramic process seal system: FKM/FPM, Kalrez® 7075, EPDM ⑤		None	Single ceramic process seal system: FKM/FPM, Kalrez® 7075, EPDM ⑤
Process connection	Stainless steel (1.4404 / 316L); HASTELLOY® C-22® [2.4602]	Stainless steel (1.4404 / 316L)	TFM-T62 PTFE-coated stainless steel (1.4404 / 316L)	Stainless steel (1.4404 / 316L) ④
Other wetted parts	PTFE			

Process connections

Thread	G 3/4...1 1/2 A (ISO 228); 3/4...1 1/2 NPT (ASME B1.20.1)
Flange version	
EN 1092-1	DN50...150 in PN10 (Type B1); DN25...150 in PN16 or PN40 (Type B1); DN50...100 in PN63 (Type B1); DN50...80 in PN100 (Type B1); others on request Optional flange facings: Types E

	Single rod Ø8 mm / 0.39"		Single rod Ø10 mm / 0.32"	Single cable Ø4 mm / 0.16"
	Single-piece	Segmented	Single-piece, fully TFM-T62 PTFE coated	
ASME B16.5	1...8" in 150 lb RF; 1...6" in 300 lb RF; 1...3" in 600 lb RF; others on request Optional flange facings: FF (Flat Face)			
JIS B2220	40...150A in 10K RF; others on request			
Other	Others on request			

Table 2-2: Technical data: Probe options - single rod and single cable probes

- ① If the device has a single rod or single cable probe option with the single ceramic process seal system, then it is not possible to measure the interface between two liquids
- ② Also depends on the temperature limits of the gasket material. Refer to "Materials" in this table and the "Process seal technical data" table.
- ③ The DNV vibration test does not include the "S" version of the device
- ④ HASTELLOY® C-22® [2.4602] is available on request
- ⑤ For more data, refer to the "Process seal technical data" table in this section

	Double cable Ø4 mm / 0.16"	Double rod Ø8 mm / 0.32")	Reversed interface Ø10 mm / 0.39"
--	-------------------------------	------------------------------	--------------------------------------

Measuring system

Application	Liquids		
Measuring range	1...14 m / 3.28...45.93 ft	0.6...4 m / 1.97...13.12 ft	1...6 m / 3.28...19.69 ft
Dead zone	This depends on the type of probe. For more data, refer to <i>Measurement limits</i> on page 28.		

Measuring accuracy

Accuracy (in direct mode)	Standard ±2 mm / ±0.08", when distance ≤ 10 m / 33 ft; ±0.02% of measured distance, when distance > 10 m / 33 ft	—
	Interface ±5 mm / ±0.2", when distance ≤ 10 m / 33 ft; ±0.05% of measured distance, when distance > 10 m / 33 ft	±5 mm / ±0.2" ①
Accuracy (in TBF mode)	±20 mm / ±0.8"	—
Minimum layer (interface)	50 mm / 2"	70 mm / 3" (for top and bottom liquids)
Resolution	0.1 mm / 0.004"	
Repeatability	±1 mm / ±0.04"	
Maximum rate of change at 4 mA	100 m/min / 328 ft/min	
Reference conditions acc. to EN 61298-1		
Temperature	+15...+25°C / +59...+77°F	
Pressure	1013 mbara ±50 mbar / 14.69 psia ±0.73 psi	
Relative air humidity (RH)	60% ±15%	
Target	Metal plate	

	Double cable Ø4 mm / 0.16"	Double rod Ø8 mm / 0.32"	Reversed interface Ø10 mm / 0.39"
--	-------------------------------	-----------------------------	--------------------------------------

Operating conditions

Min./Max. temperature at the process connection ②	-50...+200°C / -58...+392°F	-50...+250°C / -58...+482°F	-50...+150°C / -58...+302°F
Pressure	Single PTFE process seal system: -1...40 barg / -14.5...580 psig		—
	Single ceramic process seal system: -1...100 barg / -14.5...1450 psig		
Viscosity (liquids only)	5000 mPa·s / 5000 cP		
Dielectric constant (ϵ_r)	≥ 1.4 in direct mode (interface: $\epsilon_r(\text{interface}) \gg \epsilon_r(\text{level})^2$)		Bottom product: $1.4 \leq \epsilon_r \leq 10$ Top product: ≤ 20
	≥ 1.1 in TBF mode		—
Vibration resistance	EN 60721-3-4, Category 4M4 (5...8.51 Hz: ± 3.5 mm / 8.51...200 Hz: 1g; 15g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g) ③	EN 60721-3-4, Category 4M3 (5...8.22 Hz: ± 0.75 mm / 8.22...200 Hz: 0.2g; 5g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g) ③	EN 60721-3-4, Category 4M4 (5...8.51 Hz: ± 3.5 mm / 8.51...200 Hz: 1g; 15g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g) ③

Materials

Probe	Stainless steel (1.4401 / 316)	Stainless steel (1.4404 / 316L)	Stainless steel (1.4404 / 316L) ④
Spacers	FEP	PTFE	PTFE
Gasket (process seal)	Single PTFE process seal system: FKM/FPM, Kalrez® 6375, EPDM ⑤		
	Single ceramic process seal system: FKM/FPM, Kalrez® 7075, EPDM ⑤		—
Process connection	Stainless steel (1.4404 / 316L)		Stainless steel (1.4404 / 316L) ④
Other wetted parts	PTFE		

Process connections

Thread	G 1 1/2 A (ISO 228); 1 1/2 NPT (ASME B1.20.1)	G 2 A...2 1/2 A (ISO 228); 2...2 1/2 NPT (ASME B1.20.1)
Flange version		
EN 1092-1	DN50...150 in PN10, PN16 or PN40 (Type B1); DN50...100 in PN63 (Type B1); DN50...80 in PN100 (Type B1); others on request Optional flange facings: Types E	DN50...200 in PN16 or PN40 (Type B1); others on request Optional flange facings: Types E
ASME B16.5	2...8" in 150 lb RF; 2...6" in 300 lb RF; 2...3" in 600 lb RF; others on request Optional flange facings: FF (Flat Face)	2...8" in 150 lb RF or 300 lb RF; others on request Optional flange facings: FF (Flat Face)

	Double cable Ø4 mm / 0.16"	Double rod Ø8 mm / 0.32"	Reversed interface Ø10 mm / 0.39"
JIS B2220	40...150A in 10K RF; others on request		50...150A in 10K RF; others on request
Other	Others on request		

Table 2-3: Technical data: Probe options - double rod, double cable and reversed interface probes

- ① If the dielectric constant value of the bottom liquid stays constant
 ② Also depends on the temperature limits of the gasket material. Refer to "Materials" in this table and the "Process seal technical data" table.
 ③ The DNV vibration test does not include the "S" version of the device
 ④ HASTELLOY® C-22® (2.4602) is available on request
 ⑤ For more data, refer to the "Process seal technical data" table in this section

	Coaxial		
	Ø22 mm / 0.87"		Ø42 mm / 1.65"
	Single-piece	Segmented	Single-piece

Measuring system

Application	Liquids	
Measuring range	0.3...6 m / 0.98...19.69 ft	0.6...6 m / 1.97...19.69 ft
Dead zone	This depends on the type of probe. For more data, refer to <i>Measurement limits</i> on page 28.	

Measuring accuracy

Accuracy (in direct mode)	Standard ±2 mm / ±0.08", when distance ≤ 10 m / 33 ft; ±0.02% of measured distance, when distance > 10 m / 33 ft Interface ±5 mm / ±0.2", when distance ≤ 10 m / 33 ft; ±0.05% of measured distance, when distance > 10 m / 33 ft
Accuracy (in TBF mode)	±20 mm / ±0.8"
Resolution	0.1 mm / 0.004"
Repeatability	±1 mm / ±0.04"
Maximum rate of change at 4 mA	100 m/min / 328 ft/min
Reference conditions acc. to EN 61298-1	
Temperature	+15...+25°C / +59...+77°F
Pressure	1013 mbara ±50 mbar / 14.69 psia ±0.73 psi
Relative air humidity (RH)	60% ±15%
Target	Water

Operating conditions

Min./Max. temperature at the process connection ①	-50...+250°C / -58...+482°F
---	-----------------------------

	Coaxial		
	Ø22 mm / 0.87"		Ø42 mm / 1.65"
	Single-piece	Segmented	Single-piece
Pressure	Single PTFE process seal system: -1...40 barg / -14.5...580 psig Single ceramic process seal system: -1...100 barg / -14.5...1450 psig		
Viscosity (liquids only)	500 mPa·s / 500 cP		2000 mPa·s / 2000 cP
Dielectric constant (ϵ_r)	≥ 1.3 in direct mode (interface: $\epsilon_r(\text{interface}) \gg \epsilon_r(\text{level})^2$) ≥ 1.1 in TBF mode		
Vibration resistance	EN 60721-3-4, Category 4M4 (5...8.51 Hz: ± 3.5 mm / 8.51...200 Hz: 1g; 15g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g) ②	EN 60721-3-4, Category 4M3 (5...8.22 Hz: ± 0.75 mm / 8.22...200 Hz: 0.2g; 5g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g)	EN 60721-3-4, Category 4M4 (5...8.51 Hz: ± 3.5 mm / 8.51...200 Hz: 1g; 15g shock $\frac{1}{2}$ sinus: 6 ms) DNVGL-CG-0339, Class A (5...13.2 Hz: ± 0.5 mm / 13.2...100 Hz: 0.7g)

Materials

Probe	Stainless steel (1.4404 / 316L); HASTELLOLOY® C-22® (2.4602)	Stainless steel (1.4404 / 316L)	Stainless steel (1.4404 / 316L); HASTELLOLOY® C-22® (2.4602)
Spacers	PTFE	PTFE	PTFE (<250°C / 482°F)
Gasket (process seal)	Single PTFE process seal system: FKM/FPM, Kalrez® 6375, EPDM ③ Single ceramic process seal system: FKM/FPM, Kalrez® 7075, EPDM ③		
Process connection	Stainless steel (1.4404 / 316L); HASTELLOLOY® C-22® (2.4602)	Stainless steel (1.4404 / 316L)	Stainless steel (1.4404 / 316L); HASTELLOLOY® C-22® (2.4602)
Other wetted parts	PTFE		

Process connections

Thread	G 3/4...1 1/2 A (ISO 228); 3/4...1 1/2 NPT (ASME B1.20.1)	G 1 1/2 A (ISO 228)
Flange version		
EN 1092-1	DN50...150 in PN10 (Type B1); DN25...150 in PN16 or PN40 (Type B1); DN50...100 in PN63 (Type B1); DN50...80 in PN100 (Type B1); others on request Optional flange facings: Types E	DN50...150 in PN10, PN16 or PN40 (Type B1); DN50...100 in PN63 (Type B1); DN50...80 in PN100 (Type B1); others on request Optional flange facings: Types E
ASME B16.5	1...8" in 150 lb RF; 1...6" in 300 lb RF; 1...3" in 600 lb RF; others on request Optional flange facings: FF (Flat Face)	2...8" in 150 lb RF; 2...6" in 300 lb RF; 2...3" in 600 lb RF; others on request Optional flange facings: FF (Flat Face)
JIS B2220	40...150A in 10K RF; others on request	50...150A in 10K RF; others on request

	Coaxial		
	Ø22 mm / 0.87"		Ø42 mm / 1.65"
	Single-piece	Segmented	Single-piece
Other	Others on request		

Table 2-4: Technical data: Probe options - coaxial probes

- ① Also depends on the temperature limits of the gasket material. Refer to "Materials" in this table and the "Process seal technical data" table.
 ② The DNV vibration test does not include the "S" version of the device
 ③ For more data, refer to the "Process seal technical data" table in this section

Process seal technical data

Sealing system	Process seal material	Process pressure range		Process connection temperature range	
		[barg]	[psig]	[°C]	[°F]
Single (PTFE)	FKM/FPM	-1...40	-14.5...580	-40...+150	-40...+302
	Kalrez® 6375			-20...+150	-4...+302
	EPDM			-50...+150	-58...+302
	TFM-T62 PTFE-coated			-50...+150	-58...+302
Single (Ceramic) ①	FKM/FPM	-1...100	-14.5...1450	-40...+200	-40...+392
	Kalrez® 7075			-20...+250	-4...+482
	EPDM			-50...+150	-58...+302

Table 2-5: Technical data: Process seal

- ① This includes a temperature extension

Process connection options: flange facing finish

Type (flange facing)	Flange facing finish, R_a (min...max)	
	[µm Rz]	[µin - AARH]

EN 1092-1

B1	3.2...12.5	125...500
E	12.5...50	500...2000

ASME B16.5

RF or FF	3.2...6.3	125...250
RJ	≤ 1.6	≤ 63

JIS B2220

RF	3.2...6.3	125...250
----	-----------	-----------

Table 2-6: Process connection options: flange facing finish

2.2 Minimum power supply voltage

Use these graphs to find the minimum power supply voltage for a given current output load.

Non-Ex and Hazardous Location approved (Ex i / IS / NI) devices




Figure 2-1: Non-Ex and Hazardous Location approval (Ex i / IS / NI): minimum power supply voltage for an output of 22 mA (switch output - relay option: 30 mA) at the terminals

X: Power supply U [V DC]

Y: Current output load R_L [Ω]

① Output 1: 4...20 mA/HART

Output 2: 4...20 mA (NOTE: use a separate power supply to energize output 2)

② Input 2: switch output - relay option

Hazardous Location (Ex d / XP/ DIP) approved devices




Figure 2-2: Non-Ex and Hazardous Location approval (Ex d / XP/ DIP): minimum power supply voltage for an output of 22 mA (switch output - relay option: 30 mA) at the terminals

X: Power supply U [V DC]

Y: Current output load R_L [Ω]

① Output 1: 4...20 mA/HART

② Output 2: 4...20 mA (NOTE: use a separate power supply to energize output 2)

③ Input 2: switch output - relay option

2.3 Process pressure and process connection temperature limits

Make sure that the transmitters are used within their operating limits. Obey the temperature limits of the process seal and the flange.

The process connection temperature range must agree with the temperature limits of the gasket material. Limits of the gasket material are shown below each graph. For more data about pressure and temperature limits of process connections, refer to the related standards (EN 1092-1, ASME B16.5 etc.).

Pressure and temperature limits for devices with a single PTFE process seal system




Figure 2-3: Operating limits for devices with a single PTFE process seal system: graph of process pressure (barg) against process connection temperature (°C)




Figure 2-4: Operating limits for devices with a single PTFE process seal system: graph of process pressure (psig) against process connection temperature (°F)

- ① Process pressure, P_s [barg]
- ② Process connection temperature, T [°C]
- ③ Process pressure, P_s [psig]
- ④ Process connection temperature, T [°F]
- ⑤ Flange connection, PN40 (EN 1092-1) or Class 300 (ASME B16.5)
- ⑥ Flange connection, PN25 (EN 1092-1)
- ⑦ Flange connection, PN16 (EN 1092-1) or Class 150 (ASME B16.5)
- ⑧ Flange connection, PN10 (EN 1092-1)

Pressure and temperature limits for devices with a single ceramic process seal system




Figure 2-5: Operating limits for devices with single ceramic process seal system: graph of process pressure (barg) against process connection temperature (°C)




Figure 2-6: Operating limits for devices with a single ceramic process seal system: graph of process pressure (psig) against process connection temperature (°F)

- ① Process pressure, P_s [barg]
- ② Process connection temperature, T [°C]
- ③ Process pressure, P_s [psig]
- ④ Process connection temperature, T [°F]
- ⑤ Flange connection, PN100 (EN 1092-1) or Class 600 (ASME B16.5)
- ⑥ Flange connection, PN63 (EN 1092-1)
- ⑦ Flange connection, PN40 (EN 1092-1) or Class 300 (ASME B16.5)
- ⑧ Flange connection, PN25 (EN 1092-1)
- ⑨ Flange connection, PN16 (EN 1092-1) or Class 150 (ASME B16.5)
- ⑩ Flange connection, PN10 (EN 1092-1)

2.4 Measurement limits

Double cable and double rod probes




Figure 2-7: Measurement limits: double cable and double rod probes

- ① Device with a double cable probe
- ② Device with a double rod probe
- ③ **Top dead zone:** Top part of the probe where measurement is not possible
- ④ **Top non-linearity zone:** Top part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$
- ⑤ **Bottom non-linearity zone:** Bottom part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$
- ⑥ **Bottom dead zone:** Bottom part of the probe where measurement is not possible
- ⑦ Gas (Air)
- ⑧ Product
- ⑨ L, Probe length
- ⑩ Tank Height
- ⑪ **Minimum distance from the probe to a metallic tank wall:** Double cable or double rod probes = $100 \text{ mm} / 4''$

Measurement limits (dead zone) in mm and inches with a single PTFE process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ③		Bottom ⑥		Top ③		Bottom ⑥	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Double cable ①	50	1.97	80	3.15	50	1.97	120	4.72
Double rod	50	1.97	20	0.78	50	1.97	60	2.36

Table 2-7: Measurement limits (dead zone) in mm and inches with a single PTFE process seal system

- ① If the cable probe does not have a counterweight, speak or write to your local supplier for more data

Measurement limits (dead zone) in mm and inches with a single ceramic process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ③		Bottom ⑥		Top ③		Bottom ⑥	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Double cable ①	70	2.76	80	3.15	70	2.76	120	4.72
Double rod	70	2.76	20	0.78	70	2.76	60	2.36

Table 2-8: Measurement limits (dead zone) in mm and inches with a single ceramic process seal system

① If the cable probe does not have a counterweight, speak or write to your local supplier for more data

Measurement limits (non-linearity zone) in mm and inches with a single PTFE or single ceramic process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ④		Bottom ⑤		Top ④		Bottom ⑤	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Double cable ①	100	3.94	0	0	100	3.94	0	0
Double rod	100	3.94	0	0	100	3.94	0	0

Table 2-9: Measurement limits (non-linearity zone) in mm and inches with a single PTFE or single ceramic process seal system

① If the cable probe does not have a counterweight, speak or write to your local supplier for more data

80 is ϵ_r of water; 2.5 is ϵ_r of oil

If you did the Auto Setup procedure after you installed the device, the values in the tables are correct. If you did not do the Auto Setup procedure, then the values for the dead zones and the non-linearity zones increase.

The device software function "Blocking Distance" is set to a default value, which is higher than or equal to the largest dead zone. You can adjust "Blocking Distance" to agree with the dead zone (for this data, refer to the measurement limits table). For more data about the device software and default values, refer to the handbook.

Single cable and single rod probes




Figure 2-8: Measurement limits: single cable and single rod probes

- ① Device with a single cable probe
- ② Device with a single rod probe
- ③ **Top dead zone:** Top part of the probe where measurement is not possible
- ④ **Top non-linearity zone:** Top part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$
- ⑤ **Bottom non-linearity zone:** Bottom part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$
- ⑥ **Bottom dead zone:** Bottom part of the probe where measurement is not possible
- ⑦ Gas [Air]
- ⑧ Product
- ⑨ L, Probe length
- ⑩ Tank Height
- ⑪ Minimum distance from the probe to a metallic tank wall: Single cable or single rod probes = $300 \text{ mm} / 12''$

Measurement limits (dead zone) in mm and inches with a single PTFE process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ③		Bottom ⑥		Top ③		Bottom ⑥	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
$\varnothing 4 \text{ mm} / 0.16''$ single cable with a centering counterweight ①	50	1.97	85	3.35	50	1.97	165	6.50
$\varnothing 4 \text{ mm} / 0.16''$ single cable with other probe options ②	50	1.97	120	4.72	50	1.97	200	7.87
Single rod	50	1.97	20	0.79	50	1.97	60	2.36

Table 2-10: Measurement limits (dead zone) in mm and inches with a single PTFE process seal system

- ① The centering counterweight is used for installation in the measuring chamber of the BM26A-5000 and BM26A-8000 (TWIN)
- ② If the cable probe does not have a counterweight, speak or write to your local supplier for more data

Measurement limits (dead zone) in mm and inches with a single ceramic process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ③		Bottom ⑥		Top ③		Bottom ⑥	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Ø4 mm / 0.16" single cable with a centering counterweight ①	70	2.76	85	3.35	70	2.76	165	6.50
Ø4 mm / 0.16" single cable with other probe options ②	70	2.76	120	4.72	70	2.76	200	7.87
Single rod	70	2.76	20	0.79	70	2.76	60	2.36

Table 2-11: Measurement limits (dead zone) in mm and inches with a single ceramic process seal system

- ① The centering counterweight is used for installation in the measuring chamber of the BM26A-5000 and BM26A-8000 (TWIN)
 ② If the cable probe does not have a counterweight, speak or write to your local supplier for more data

Measurement limits (non-linearity zone) in mm and inches with a single PTFE process seal system

Probes	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ④		Bottom ⑤		Top ④		Bottom ⑤	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Ø4 mm / 0.16" single cable ①	150	5.91	0	0	150	5.91	0	0
Single rod	150	5.91	0	0	150	5.91	0	0

Table 2-12: Measurement limits (non-linearity zone) in mm and inches with a single PTFE process seal system

- ① If the cable probe does not have a counterweight, speak or write to your local supplier for more data

Measurement limits (non-linearity zone) in mm and inches with a single ceramic process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ④		Bottom ⑤		Top ④		Bottom ⑤	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Ø4 mm / 0.16" single cable ①	150	5.91	0	0	150	5.91	0	0
Single rod	150	5.91	0	0	150	5.91	0	0

Table 2-13: Measurement limits (non-linearity zone) in mm and inches with a single ceramic process seal system

- ① If the cable probe does not have a counterweight, speak or write to your local supplier for more data

80 is ϵ_r of water; 2.5 is ϵ_r of oil

If you did the Auto Setup procedure after you installed the device, the values in the tables are correct. If you did not do the Auto Setup procedure, then the values for the dead zones and the non-linearity zones increase. If the cable probe does not have a counterweight, speak or write to your local supplier for more data.

The device software function "Blocking Distance" is set to a default value, which is higher than or equal to the largest dead zone. You can adjust "Blocking Distance" to agree with the dead zone (for this data, refer to the measurement limits table). For more data about the device software and default values, refer to the handbook.

Coaxial probes




Figure 2-9: Measurement limits: coaxial probes

- ① Device with a coaxial probe
- ② **Top dead zone:** Top part of the probe where measurement is not possible
- ③ **Top non-linearity zone:** Top part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$
- ④ **Bottom non-linearity zone:** Bottom part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$
- ⑤ **Bottom dead zone:** Bottom part of the probe where measurement is not possible
- ⑥ Gas (Air)
- ⑦ Product
- ⑧ L, Probe length
- ⑨ Tank Height
- ⑩ Minimum distance from the probe to a metallic tank wall: Coaxial probe = $0 \text{ mm} / 0''$

Measurement limits (dead zone) in mm and inches with a single PTFE process seal system or a single ceramic process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ②		Bottom ⑤		Top ②		Bottom ⑤	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Ø22 mm / 0.87'' coaxial	50	1.97	20	0.79	50	1.97	20	0.79
Ø42 mm / 1.65'' coaxial	50	1.97	20	0.79	50	1.97	20	0.79

Table 2-14: Measurement limits (dead zone) in mm and inches with a single PTFE process seal system or a single ceramic process seal system

Measurement limits (non-linearity zone) in mm and inches with a single PTFE process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ③		Bottom ④		Top ③		Bottom ④	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Ø22 mm / 0.87" coaxial	0	0	0	0	0	0	0	0
Ø42 mm / 1.65" coaxial	0	0	0	0	0	0	0	0

Table 2-15: Measurement limits (non-linearity zone) in mm and inches with a single PTFE process seal system

Measurement limits (non-linearity zone) in mm and inches with a single ceramic process seal system

Probe	$\epsilon_r = 80$				$\epsilon_r = 2.5$			
	Top ③		Bottom ④		Top ③		Bottom ④	
	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
Ø22 mm / 0.87" coaxial	80	3.15	0	0	80	3.15	0	0
Ø42 mm / 1.65" coaxial	80	3.15	0	0	80	3.15	0	0

Table 2-16: Measurement limits (non-linearity zone) in mm and inches with a single ceramic process seal system

80 is ϵ_r of water; 2.5 is ϵ_r of oil

If you did the Auto Setup procedure after you installed the device, the values in the tables are correct. If you did not do the Auto Setup procedure, then the values for the dead zones and the non-linearity zones increase.

The device software function "Blocking Distance" is set to a default value, which is higher than or equal to the largest dead zone. You can adjust "Blocking Distance" to agree with the dead zone (for this data, refer to the measurement limits table). For more data about the device software and default values, refer to the handbook.

Reversed interface probe




Figure 2-10: Measurement limits: reversed interface probe

- ① Device with a reversed interface probe
- ② **Bottom non-linearity zone:** Bottom part of the probe with a lower accuracy of $\pm 30 \text{ mm} / \pm 1.18''$. NOTE: The reversed interface probe measures the interface level from the bottom of the probe, thus the top non-linearity zone is not applicable.
- ③ **Bottom dead zone:** Bottom part of the probe where measurement is not possible. NOTE: The reversed interface probe measures the interface level from the bottom of the probe, thus the top dead zone is not applicable.
- ④ Gas (Air)
- ⑤ Top product (high dielectric constant)
- ⑥ Bottom product (low dielectric constant)
- ⑦ L, Probe length
- ⑧ Tank Height
- ⑨ Minimum distance from the probe to a metallic tank wall: Reversed interface probe = $100 \text{ mm} / 4''$

Measurement limits (dead zone) in mm and inches

Probe	$\epsilon_r = 2.5$	
	Bottom ③	
	[mm]	[inches]
Reversed interface	100	3.94

Table 2-17: Measurement limits (dead zone) in mm and inches

Measurement limits (non-linearity zone) in mm and inches

Probe	$\epsilon_r = 2.5$	
	Bottom ②	
	[mm]	[inches]
Reversed interface	0	0

Table 2-18: Measurement limits (non-linearity zone) in mm and inches

If you did the Auto Setup procedure after you installed the device, the values in the tables are correct. If you did not do the Auto Setup procedure, then the values for the dead zones and the non-linearity zones increase.

The device software function "Blocking Distance" is set to a default value, which is higher than or equal to the largest dead zone. You can adjust "Blocking Distance" to agree with the dead zone (for this data, refer to the measurement limits table). For more data about the device software and default values, refer to the handbook.

2.5 Dimensions and weights

2.5.1 General notes

All housing covers have bayonet connectors unless it is an explosion-proof (XP / Ex d-approved) device or has the second current output / switch output (relay) option. If the device has the second current output / switch output (relay) option or has an Ex d / XP (explosion-proof) approval, the terminal compartment cover has a thread with a flame path.

2.5.2 Primary components




Figure 2-11: Primary components

- ① Signal converter. From left to right:
 - Vertical / Horizontal compact version (C)
 - Sensor extension with vertical / horizontal compact version (S) – signal converter attached to the process connection with a coaxial cable
 - Remote version (F) – signal converter attached to the probe electronics in a different housing with an RS-485 cable
 - Double sensor extension with remote version (D) – signal converter attached to the probe electronics in a different housing with an RS-485 cable which is then attached to the process connection with a coaxial cable
- ② Process connection: threaded or flange connection, including the process seal option. For more data, refer to *Technical data* on page 11.
- ③ Probe

2.5.3 Signal converter and probe electronics options

Compact version (C)




Figure 2-12: Compact version (C)

- ① Horizontal compact version
- ② Vertical compact version

If the device has the second current output / switch output (relay) option, use the dimensions given for Ex d / XP-approved devices.

Dimensions [mm]	Horizontal		Vertical	
	Non-Ex / Ex i / IS	Optional output / Ex d / XP	Non-Ex / Ex i / IS	Optional output / Ex d / XP
a	191	258	147	210
b	175	175	218	218
c	127	127 (153) ①	127	127 (153) ①

Table 2-19: Compact version (C): Dimensions in mm

- ① Use the dimension in round brackets if the device has 2 current outputs or a switch output (relay)

Dimensions [inches]	Horizontal		Vertical	
	Non-Ex / Ex i / IS	Optional output / Ex d / XP	Non-Ex / Ex i / IS	Optional output / Ex d / XP
a	7.52	10.16	5.79	8.27
b	6.89	6.89	8.23	8.23
c	5.00	5.00 (6.02) ①	5.00	5.00 (6.02) ①

Table 2-20: Compact version (C): Dimensions in inches

- ① Use the dimension in round brackets if the device has 2 current outputs or a switch output (relay)

Sensor extension with vertical compact version (S)




Figure 2-13: Sensor extension with vertical compact version (S)

If the device has the second current output / switch output (relay) option, use the dimensions given for Ex d / XP-approved devices.

	Dimensions [mm]						
	a	b	c	e	f	g	h
Non-Ex / Ex i / IS	127	254	285.4	329	89	150	150.4
Optional output / Ex d / XP	127 (153) ①	254	348.4	329	89	150	150.4

Table 2-21: Sensor extension with vertical compact version (S): Dimensions in mm

① Use the dimension in round brackets if the device has 2 current outputs or a switch output (relay)

	Dimensions [inches]						
	a	b	c	e	f	g	h
Non-Ex / Ex i / IS	5.00	10.00	11.23	12.95	3.50	5.91	5.92
Optional output / Ex d / XP	5.00 (6.02) ①	10.00	13.72	12.95	3.50	5.91	5.92

Table 2-22: Sensor extension with vertical compact version (S): Dimensions in inches

① Use the dimension in round brackets if the device has 2 current outputs or a switch output (relay)

Sensor extension with horizontal compact version (S)




Figure 2-14: Sensor extension with horizontal compact version (S)

If the device has the second current output / switch output (relay) option, use the dimensions given for Ex d / XP-approved devices.

	Dimensions [mm]						
	a	b	c	e	f	g	h
Non-Ex / Ex i / IS	127	211	281	285	89	150	150.4
Optional output / Ex d / XP	127 (153) ①	211	344	285	89	150	150.4

Table 2-23: Sensor extension with horizontal compact version (S): Dimensions in mm

① Use the dimension in round brackets if the device has 2 current outputs or a switch output (relay)

	Dimensions [inches]						
	a	b	c	e	f	g	h
Non-Ex / Ex i / IS	5.00	8.31	11.06	11.22	3.50	5.91	5.92
Optional output / Ex d / XP	5.00 (6.02) ①	8.31	13.54	11.22	3.50	5.91	5.92

Table 2-24: Sensor extension with horizontal compact version (S): Dimensions in inches

① Use the dimension in round brackets if the device has 2 current outputs or a switch output (relay)

Sensor extension with compact version (S)
Double sensor extension with remote version (D)
- wall bracket




Figure 2-15: Wall bracket

	Dimensions [mm]					
	a	b	c	d	e	f
Wall bracket	120	60	20	11	67.4	150

Table 2-25: Wall bracket: Dimension in mm

	Dimensions [mm]					
	g	h	k	m	n	
Wall bracket	126.4	150.4	90	50	6	

Table 2-26: Wall bracket: Dimension in mm

	Dimensions [inches]					
	a	b	c	d	e	f
Wall bracket	4.72	2.36	0.79	0.43	2.65	5.91

Table 2-27: Wall bracket: Dimension in inches

	Dimensions [inches]					
	g	h	k	m	n	
Wall bracket	4.98	5.92	3.54	1.97	0.24	

Table 2-28: Wall bracket: Dimension in inches

**Remote version (F)
Double sensor extension with remote version (D)
– remote converter housing**




Figure 2-16: Remote version (F) / Double sensor extension with remote version (D) – remote converter housing

If the device has the second current output / switch output (relay) option, use the dimensions given for Ex d / XP-approved devices.

Dimensions [mm]	Remote	
	Non-Ex / Ex i / IS	Optional output / Ex d / XP
d	195	195
e	146	209
f	100	100
g	130	130

Table 2-29: Remote converter housing (device versions F" and "D"): Dimensions in mm

Dimensions [inches]	Remote	
	Non-Ex / Ex i / IS	Optional output / Ex d / XP
d	7.68	7.68
e	5.75	8.23
f	3.94	3.94
g	5.12	5.12

Table 2-30: Remote converter housing (device versions F" and "D"): Dimensions in inches

Remote version (F) – probe electronics housing




Figure 2-17: Remote version (F) – probe electronics housing

Dimensions [mm]	Remote	
	Non-Ex / Ex i / IS	Ex d / XP
a	104	104
b	142	142
c	129	129

Table 2-31: Probe electronics housing (device version "F"): Dimensions in mm

Dimensions [inches]	Remote	
	Non-Ex / Ex i / IS	Ex d / XP
a	4.09	4.09
b	5.59	5.59
c	5.08	5.08

Table 2-32: Probe electronics housing (device version "F"): Dimensions in inches

Double sensor extension with remote version (D) – probe electronics housing




Figure 2-18: Double sensor extension with remote version (D) – probe electronics housing

For more dimensional data about the wall bracket, refer to "Sensor extension with vertical compact version (S) / Double sensor extension with remote version (D) - wall bracket" in this section.

	Dimensions [mm]					
	a	b	c	h	k	m
Probe electronics housing with sensor extension	252.3	177.3	241	150.4	88.9	150

Table 2-33: Probe electronics housing (device version "D"): Dimensions in mm

	Dimensions [inches]					
	a	b	c	h	k	m
Probe electronics housing with sensor extension	9.93	6.98	9.49	5.92	3.50	5.91

Table 2-34: Probe electronics housing (device version "D"): Dimensions in inches

Converter and probe electronics housing weights

Type of housing	Weights			
	Aluminium housing		Stainless-steel housing	
	[kg]	[lb]	[kg]	[lb]

One output / Non-Ex / intrinsically-safe (Ex i / IS)

Compact converter	2.8	6.2	6.4	14.1
Remote converter ①	2.5	5.5	5.9	13.0
Probe electronics housing ①	1.8	4.0	3.9	8.6

Optional output / Explosion proof (Ex d / XP)

Compact converter	3.2	7.1	7.5	16.5
Remote converter ①	2.9	6.40	7.1	15.65
Probe electronics housing ①	1.8	4.0	3.9	8.6

Table 2-35: Converter and probe electronics housing weights in kg and lb

① The remote version of the device has a "remote converter" and a "probe electronics housing". For more data, refer to "Housing dimensions" at the start of this section.

2.5.4 Process connection options




Figure 2-19: Process connection options

h = height of process connection

L = probe length

- ① Threaded connection with single PTFE process seal system
- ② Threaded connection with single ceramic process seal system
- ③ Flange with single PTFE process seal system
- ④ Flange with single ceramic process seal system

Probe option: PTFE-coated single rod probe

A device with this probe option can only have a flange with a single PTFE process seal system.

Probe option: Reversed interface probe

A device with this probe option can only have a threaded connection or flange with a single PTFE process seal system.

Process connection	Process seal system	Dimensions [mm]	
		h	L
Threaded connection	Single PTFE	44.2	①
	Single Ceramic	223.7	
Flange	Single PTFE	72.5	①
	Single Ceramic	252	

Table 2-36: Process connection options: Dimensions in mm

① Refer to "Probe options" in this chapter

Process connection	Process seal system	Dimensions [inches]	
		h	L
Threaded connection	Single PTFE	1.74	①
	Single Ceramic	8.10	
Flange	Single PTFE	2.85	①
	Single Ceramic	9.92	

Table 2-37: Process connection options: Dimensions in inches

① Refer to "Probe options" in this chapter

2.5.5 Probe options

Single probes: options and overall dimensions




Figure 2-20: Single probes: options and overall dimensions

- ① Single rod $\varnothing 8$ mm / $\varnothing 0.32$ "
- ② Single cable $\varnothing 4$ mm / $\varnothing 0.16$ "
- ③ Single rod $\varnothing 8$ mm / $\varnothing 0.32$ " (segmented version)
- ④ Single rod $\varnothing 10$ mm / $\varnothing 0.39$ " with PTFE coating – only available with a flange and a single PTFE process seal system

Probe length, L, includes the length of the counterweight.

A wide range of counterweights are available. For dimensional data, refer to the pages that follow. For installation data, refer to the handbook.

Probes	Dimensions [mm]			
	L min.	L max.	m	t
Single rod Ø8 mm	600	4000	—	—
Single cable Ø4 mm	1000	60000	①	②
Single rod Ø8 mm (segmented version)	600	6000	—	—
Single rod Ø8 mm with PTFE coating	600	4000	—	—


Table 2-38: Single probes: options and overall dimensions in mm

- ① If the probe has the standard counterweight option, then $m = 100$ mm. If the probe has the centering counterweight option, then $m = 65$ mm.
- ② If the probe has the standard counterweight option, then $t = \text{Ø}20$ mm. If the probe has the standard counterweight option, then $t = \text{Ø}30$ mm.

Probes	Dimensions [inches]			
	L min.	L max.	m	t
Single rod Ø0.32"	24	158	—	—
Single cable Ø0.16"	39	2362	①	②
Single rod Ø0.32" (segmented version)	24	236	—	—
Single rod Ø0.32" with PTFE coating	24	158	—	—

Table 2-39: Single probes: options and overall dimensions in inches

- ① If the probe has the standard counterweight option, then $m = 3.9$ ". If the probe has the centering counterweight option, then $m = 2.6$ ".
- ② If the probe has the standard counterweight option, then $t = \text{Ø}0.8$ ". If the probe has the standard counterweight option, then $t = \text{Ø}1.2$ ".

Probe end options for the $\varnothing 4$ mm / 0.16" single cable probeFigure 2-21: Probe end options for the $\varnothing 4$ mm / 0.16" single cable probe

- ① Standard counterweight
- ② Centering counterweight - for installation in the measuring chamber of the BM26A-5000 and BM26A-8000 (TWIN)
- ③ Threaded end
- ④ Crimped end
- ⑤ Open end
- ⑥ Turnbuckle
- ⑦ Chuck

Probe end type	Dimensions [mm]		
	n	t	v
Standard counterweight	100	Ø20	—
Centering counterweight	65	Ø30	—
Threaded end	70	M8	—
Crimped end	55	Ø8	—
Open end	—	—	—
Turnbuckle	172 ①	11	Ø6
Chuck	300	—	—

Table 2-40: Probe end options for the Ø4 mm / 0.16" single cable probe: Dimensions in mm

① Minimum length

Probe end type	Dimensions [inches]		
	n	t	v
Standard counterweight	3.9	Ø0.8	—
Centering counterweight	2.6	Ø1.2	—
Threaded end	2.8	M8	—
Crimped end	2.2	Ø0.3	—
Open end	—	—	—
Turnbuckle	6.8 ①	0.4	Ø0.2
Chuck	11.8	—	—

Table 2-41: Probe end options for the Ø4 mm / 0.16" single cable probe: Dimensions in inches

① Minimum length

Double probes and coaxial probes: options and overall dimensions




Figure 2-22: Double probes and coaxial probes: options and overall dimensions

- ① Double cable $\varnothing 4$ mm / $\varnothing 0.16$ "
- ② Double rod $\varnothing 8$ mm / $\varnothing 0.32$ "
- ③ Coaxial $\varnothing 22$ mm / $\varnothing 0.87$ "
- ④ Coaxial $\varnothing 22$ mm / $\varnothing 0.87$ " (segmented version)
- ⑤ Coaxial $\varnothing 42$ mm / $\varnothing 1.65$ "
- ⑥ Reversed interface $\varnothing 10$ mm / $\varnothing 0.39$ "

Cable probes: Probe length, L, includes the length of the counterweight.

A wide range of counterweights and anchoring solutions are available. For dimensional data, refer to the pages that follow. For installation data, refer to the handbook.

Probes	Dimensions [mm]					
	L min.	L max.	q	s	t	u
Double cable Ø4 mm	1000 ①	14000	60	—	Ø38	—
Double rod Ø8 mm	600 ①	4000	—	—	25	—
Coaxial Ø22 mm	300 ①	6000	—	20	—	Ø6
Coaxial Ø22 mm (segmented) ②	300 ①	6000	—	20	Ø28	Ø6
Coaxial Ø42 mm	600 ①	6000	—	30	—	Ø15
Reversed interface Ø10 mm	1000 ①	6000	—	—	—	—

Table 2-42: Double probes and coaxial probes: options and overall dimensions in mm

① A shorter probe length is available on request

② The length of each segment is 700 mm. A device with this probe option must be assembled on site. For the assembly procedure, refer to the handbook or the printed procedure supplied with the components.

Probes	Dimensions [inches]					
	L min.	L max.	q	s	t	u
Double cable Ø0.16"	39 ①	551	2.4	—	Ø1.5	—
Double rod Ø0.32"	24 ①	158	—	—	1.0	—
Coaxial Ø0.87"	12 ①	236	—	0.8	—	Ø0.2
Coaxial Ø0.87" (segmented) ②	12 ①	236	—	0.8	Ø1.1	Ø0.2
Coaxial Ø1.65"	24 ①	236	—	1.2	—	Ø0.6
Reversed interface Ø0.39"	39 ①	236	—	—	—	—

Table 2-43: Double probes and coaxial probes: options and overall dimensions in inches

① A shorter probe length is available on request

② The length of each segment is 27.6". A device with this probe option must be assembled on site. For the assembly procedure, refer to the handbook or the printed procedure supplied with the components.

Probe weights

Probes	Process seal system	Process connection	Process connection weights		Probe Weights	
			[kg]	[lb]	[kg/m]	[lb/ft]
Coaxial Ø42 mm / Ø1.65"	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	3.2 ①	2.15 ①
		Flange	1.6...34.6	3.5...76.3		
	Single seal (ceramic)	Threaded	2.0...2.5	4.4...5.5		
		Flange	3.0...36.0	6.6...79.4		
Single rod Ø8 mm / Ø0.32" (single-piece or segmented)	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	0.41 ①	0.28 ①
		Flange	1.6...34.6	3.5...76.3		
	Single seal (ceramic)	Threaded	2.0...2.5	4.4...5.5		
		Flange	3.0...36.0	6.6...79.4		
Single rod Ø10 mm / Ø0.39" (PTFE-coated)	Single seal (PTFE)	Flange	1.6...34.6	3.5...76.3	0.5 ①	0.34 ①
Single cable Ø4 mm / Ø0.16"	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	0.12 ②	0.08 ②
		Flange	1.6...34.6	3.5...76.3		
	Single seal (ceramic)	Threaded	2.0...2.5	4.4...5.5		
		Flange	3.0...36.0	6.6...79.4		
Coaxial Ø22 mm / Ø0.87" (single-piece or segmented)	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	0.79 ①	0.53 ①
		Flange	1.6...34.6	3.5...76.3		
	Single seal (ceramic)	Threaded	2.0...2.5	4.4...5.5		
		Flange	3.0...36.0	6.6...79.4		
Double rod Ø8 mm / Ø0.32"	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	0.82 ①	0.56 ①
		Flange	1.6...34.6	3.5...76.3		
	Single seal (ceramic)	Threaded	2.0...2.5	4.4...5.5		
		Flange	3.0...36.0	6.6...79.4		
Double cable Ø4 mm / Ø0.16"	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	0.24 ②	0.16 ②
		Flange	1.6...34.6	3.5...76.3		
	Single seal (ceramic)	Threaded	2.0...2.5	4.4...5.5		
		Flange	3.0...36.0	6.6...79.4		
Reversed interface Ø10 mm / Ø0.39"	Single seal (PTFE)	Threaded	0.6...1.0	1.3...2.2	1.1 ①	0.74 ①
		Flange	1.6...34.6	3.5...76.3		

Table 2-44: Probe weights

① This value does not include the weight of the process connection

② This value does not include the weights of the counterweight or the process connection

2.5.6 Weather protection option

Vertical signal converters




Figure 2-23: Vertical signal converters

- ① Non-Ex / Ex i / IS: Rear view (with weather protection closed)
- ② Non-Ex / Ex i / IS: Right side (with weather protection closed)
- ③ Non-Ex / Ex i / IS: Front view (with weather protection closed)
- ④ Optional output / Ex d / XP: Rear view (with weather protection closed)
- ⑤ Optional output / Ex d / XP: Right side (with weather protection closed)
- ⑥ Optional output / Ex d / XP: Front view (with weather protection closed)

Weather protection	Version	Dimensions [mm]				Weights [kg]
		a	b	c	d	
Vertical signal converter	Non-Ex / Ex i / IS	241	118	96	77	1.3
	Optional output / Ex d / XP	241	118	166	77	1.5

Table 2-45: Vertical signal converters: Dimensions and weights in mm and kg

Weather protection	Version	Dimensions [inches]				Weights [lb]
		a	b	c	d	
Vertical signal converter	Non-Ex / Ex i / IS	9.5	4.6	3.8	3.0	2.9
	Optional output / Ex d / XP	9.5	4.6	6.5	3.0	3.3

Table 2-46: Vertical signal converters: Dimensions and weights in inches and lb

Horizontal signal converters




Figure 2-24: Horizontal signal converters

- ① Non-Ex / Ex i / IS: Front view (with weather protection closed)
- ② Non-Ex / Ex i / IS: Left side (with weather protection closed)
- ③ Non-Ex / Ex i / IS: Rear view (with weather protection closed)
- ④ Optional output / Ex d / XP: Front view (with weather protection closed)
- ⑤ Optional output / Ex d / XP: Left side (with weather protection closed)
- ⑥ Optional output / Ex d / XP: Rear view (with weather protection closed)

Weather protection	Version	Dimensions [mm]				Weights [kg]
		a	b	c	d	
Horizontal signal converter	Non-Ex / Ex i / IS	243	118	96	77	1.3
	Optional output / Ex d / XP	243	118	166	77	1.5

Table 2-47: Horizontal signal converters: Dimensions and weights in mm and kg

Weather protection	Version	Dimensions [inches]				Weights [lb]
		a	b	c	d	
Horizontal signal converter	Non-Ex / Ex i / IS	9.6	4.6	3.8	3.0	2.9
	Optional output / Ex d / XP	9.6	4.6	6.5	3.0	3.3

Table 2-48: Horizontal signal converters: Dimensions and weights in inches and lb

3.1 Intended use

Responsibility for the use of the measuring devices with regard to suitability, intended use and corrosion resistance of the used materials against the measured fluid lies solely with the operator.

The manufacturer is not liable for any damage resulting from improper use or use for other than the intended purpose.

This TDR level transmitter measures distance, level, interface, mass and volume of liquids, pastes and slurries.

It can be installed on tanks and reactors.

3.2 How to prepare the tank before you install the device

To avoid measuring errors and device malfunction, obey these precautions.

3.2.1 General information for nozzles

Follow these recommendations to make sure that the device measures correctly. They have an effect on the performance of the device.

Do not put the process connection near to the product inlet. If the product that enters the tank touches the probe, the device will measure incorrectly.




Figure 3-1: Do not put the device near to a product inlet

- ① The device is in the correct position.
- ② The device is too near to the product inlet.
- ③ If it is not possible to put the device in the recommended position, install a deflector pipe.




Figure 3-2: How to prevent build-up of product around the process connection

- ① If product particles are likely to collect in holes, a nozzle is not recommended.
- ② Attach the flange directly to the tank.
- ③ Use a threaded connection to attach the device directly to the tank.

For single cable and single rod probes:




Figure 3-3: Recommended nozzle dimensions for single rod and single cable probes

- ① Recommended conditions: $h \leq d$, where h is the height of the tank nozzle and d is the diameter of the tank nozzle.
- ② The end of the nozzle must not have an extension into the tank. Do not install the device on a high nozzle.

If the device is installed on a high nozzle, make sure that the probe does not touch the side of the nozzle (attach the probe end etc.).



Figure 3-4: Sockets for threaded process connections

- ① Recommended installation
- ② The end of the socket must not have an extension into the tank

For double cable and double rod probes:




Figure 3-5: Recommended nozzle dimensions for double rod and double cable probes

- If $50 \text{ mm} < d < 100 \text{ mm}$ / $2'' < d < 3.9''$, then $h < d$
 - If $d \geq 100 \text{ mm}$ / $3.9''$, then there is no maximum limit for h
- where "h" is the nozzle height and "d" is the diameter of the tank nozzle

For coaxial probes:

If your device has a coaxial probe, you can ignore the installation recommendations in this section. But:

Install the $\varnothing 22 / 0.87''$ coaxial probe in clean liquids that have a viscosity less than $500 \text{ Pa}\cdot\text{s}$ / 500 cP . Install the $\varnothing 42 / 1.65''$ coaxial probe in clean liquids that have a viscosity less than $2000 \text{ Pa}\cdot\text{s}$ / 2000 cP .

For reversed interface probes:




Figure 3-6: Minimum limits for the installation of the reversed interface probe

- ① Minimum distance between the end of the probe and the tank bottom: 100 mm / $3.9''$

3.3 Installation recommendations for liquids

3.3.1 General requirements




Figure 3-7: Installation recommendations for liquids

- ① The electromagnetic (EM) field generated by the device. It has a radius of R_{min} . Make sure that the EM field is clear of objects and product flow. Refer to the table that follows.
- ② If there are too many objects in the tank, install a bypass chamber or stilling well
- ③ Keep the probe straight. If the probe is too long, shorten the probe length. Make sure that the device is configured with the new probe length. For more data on the procedure, refer to the handbook.
- ④ Empty space. Refer to the table that follows.

Clearance between the probe and other objects in the tank

Probe type	Empty space (radius, R_{min}), around the probe	
	[mm]	[inches]
Coaxial	0	0
Double rod / cable	100	4
Reversed interface	100	4
Single rod / cable	300	12

Table 3-1: Clearance between the probe and other objects in the tank

3.3.2 Installation in standpipes (stilling wells and bypass chambers)

Use a standpipe if:

- The liquid is very turbulent or agitated.
- There are too many other objects in the tank.
- The device is measuring a liquid in a tank with a floating roof.




Figure 3-8: Installation recommendations for standpipes (stilling wells and bypass chambers)

- ① Stilling well
- ② Bypass chamber
- ③ Vent
- ④ Level of the liquid

Stilling wells are not necessary for devices with coaxial probes. But if there is a sudden change in diameter in the stilling well, we recommend that you install a device with a coaxial probe.

- *The standpipe must be electrically conductive. If the standpipe is not made of metal, obey the instructions for empty space around the probe. For more data, refer to General requirements on page 58.*
- *The standpipe must be straight. There must be no changes in diameter from the device process connection to the bottom of the standpipe.*
- *The standpipe must be vertical.*
- *Recommended surface roughness: $< \pm 0.1 \text{ mm} / 0.004''$.*
- *The bottom of the stilling well must be open.*
- *Adjust the probe to the center of the standpipe.*
- *Make sure that there are no deposits at the bottom of the standpipe which can cause blockage of the process connections.*
- *Make sure that there is liquid in the standpipe.*

Floating roofs

If the device is for a tank with a floating roof, install it in a stilling well.




Figure 3-9: Floating roofs

- ① Sediment
- ② Support fixtures
- ③ Stilling well
- ④ Floating roof
- ⑤ Product
- ⑥ Tank

4.1 Electrical installation: 2-wire, loop-powered

4.1.1 Compact version

Output 1 energizes the device and is used for HART® communication. If the device has the second current output option, use a separate power supply to energize output 2. If the device has a switch output - relay option, use a separate power supply (connect the power supply to the switch power supply terminals).

Terminals for electrical installation (one output)




Figure 4-1: Terminals for electrical installation (one output)

- ① Current output 1
- ② Grounding terminal in the housing (if the electrical cable is shielded)
- ③ Location of the external grounding terminal (at the bottom of the converter)

Terminals for electrical installation (two current outputs)




Figure 4-2: Terminals for electrical installation (two current outputs)

- ① Output 1: Terminals
- ② Output 2: Terminals
- ③ Location of the external grounding terminal (at the bottom of the converter)
- ④ Grounding terminal in the housing (if the electrical cable is shielded)

Terminals for electrical installation (one current output and one switch output - relay)




Figure 4-3: Terminals for electrical installation (one current output and one switch output - relay)

- ① Current output 1: Terminals
- ② Switch power supply: Terminals
- ③ Switch output - relay: Terminals
- ④ Location of the external grounding terminal (at the bottom of the converter)
- ⑤ Grounding terminal in the housing (if the electrical cable is shielded)

4.1.2 Remote version

Output 1 energizes the device and is used for HART® communication. If the device has the second current output option, use a separate power supply to energize output 2. If the device has a switch output - relay option, use a separate power supply (connect the power supply to the switch power supply terminals).

Terminals for electrical installation (one output)




Figure 4-4: Terminals for electrical installation (one output)

- ① Current output 1: Terminals
- ② Grounding terminal in the housing (if the electrical cable is shielded)
- ③ Location of the external grounding terminal (on the wall support)

Terminals for electrical installation (two current outputs)




Figure 4-5: Terminals for electrical installation (two current outputs)

- ① Output 1: Terminals
- ② Output 2: Terminals
- ③ Location of the external grounding terminal (on the wall support)
- ④ Grounding terminal in the housing (if the electrical cable is shielded)

Terminals for electrical installation (one current output / one switch output - relay)




Figure 4-6: Terminals for electrical installation (one current output / one switch output - relay)

- ① Current output 1: Terminals
- ② Switch power supply: Terminals
- ③ Switch output - relay: Terminals
- ④ Location of the external grounding terminal (on the wall support)
- ⑤ Grounding terminal in the housing (if the electrical cable is shielded)

Connections between the remote converter and the probe housing (one output)




Figure 4-7: Connections between the remote converter and the probe housing (one output)

- ① Remote converter
- ② Probe housing
- ③ Power supply: voltage in -
- ④ Power supply: voltage in +
- ⑤ Signal cable B
- ⑥ Signal cable A
- ⑦ Shielding wire (attached to Faston connectors in the housings of the remote converter and the probe housing)

For more electrical installation data, refer to *Compact version* on page 61.

4.2 Non-Ex devices

Two current outputs and the switch output - relay are supplied together as a device option. Two current outputs or the switch output - relay are only available if you send an order for a device with these options.

For more data about current output functions, the switch function and related settings, refer to the "Operation" chapter in the handbook.

One current output




Figure 4-8: Electrical connections for non-Ex devices (one current output)

- ① Power supply
- ② Resistor for HART® communication
- ③ Optional connection to the grounding terminal
- ④ Output: 11.5...30 V DC for an output of 22 mA at the terminal
- ⑤ Device

Two current outputs




Figure 4-9: Electrical connections for non-Ex devices (two current outputs)

- ① Power supply
- ② Resistor for HART® communication
- ③ Optional connection to the grounding terminal
- ④ Output 1 and 2: 11.5...30 V DC for an output of 22 mA at the terminals

Note: Use a separate power supply to energize output 2. Make sure that the two outputs are energized.

- ⑤ Device
- ⑥ Connector for the optional second output

One current output and one switch output - relay




Figure 4-10: Electrical connections for non-Ex devices (one current output and one switch output - relay)

- ① Power supply
- ② Resistor for HART® communication
- ③ Optional connection to the grounding terminal
- ④ Output 1: 11.5...30 V DC for an output of 22 mA at the terminals
- ⑤ Switch power supply [2]: 11.5...34 V DC / 30 mA

Note: Use a separate power supply to energize the switch output - relay option. Make sure that the current output and the switch power supply terminals are energized.

- ⑥ Device
- ⑦ Connector for the switch output - relay
- ⑧ PLC (for example)

4.3 Devices for hazardous locations

For electrical data for device operation in hazardous locations, refer to the related certificates of compliance and supplementary instructions (ATEX, IECEx etc.). This documentation can be downloaded from the website (Download Center).

4.4 Networks

4.4.1 General information

The device uses the HART® communication protocol. This protocol agrees with the HART® Communication Foundation standard. The device can be connected point-to-point. It can also have a polling address of 1 to 63 in a multi-drop network.

The device output is factory-set to communicate point-to-point. To change the communication mode from **point-to-point** to **multi-drop**, refer to "Network configuration" in the handbook.

4.4.2 Point-to-point networks




Figure 4-11: Point-to-point connection

- ① Address of the device (0 for a point-to-point connection)
- ② 4...20 mA + HART®
- ③ Resistor for HART® communication
- ④ Power supply
- ⑤ HART® modem
- ⑥ HART® communication device

4.4.3 Multi-drop networks




Figure 4-12: Multi-drop network (non-Ex)

- ① Address of the device (n+1 for multidrop networks)
- ② Address of the device (1 for multidrop networks)
- ③ 4 mA + HART®
- ④ Resistor for HART® communication
- ⑤ Power supply
- ⑥ HART® modem
- ⑦ HART® communication device

KROHNE – Products, Solutions and Services

- Process instrumentation for flow, level, temperature, pressure measurement and process analytics
- Flow metering, monitoring, wireless and remote metering solutions
- Engineering, commissioning, calibration, maintenance and training services

Head Office KROHNE Messtechnik GmbH
Ludwig-Krohne-Str. 5
47058 Duisburg (Germany)
Tel.: +49 203 301 0
Fax: +49 203 301 10389
info@krohne.de

The current list of all KROHNE contacts and addresses can be found at:
www.krohne.com

